



- MSTKN - H - S14 - HM - DB25M - OP
- Enclosure**
 - H = Aluminium enclosure
 - P = Enclosure vor variable trays
 - Socket tray type**
 - S = Single plugs Ø 38mm
 - T = Common block for standard bits
 - P = variable prismatic tray
 - M = Medium custom sockets
 - L = Large custom sockets
 - Socket number**
 - 13 = single row, 3 sockets
 - 14 = single row, 4 sockets
 - 18 = single row, 8 sockets
 - 24 = zwo rows, 4 sockets per row (total: 8 sockets)
 - Options**
 - (none) standard
 - OP = Open Protocol
 - Interface type**
 - Only for Modules HM and GM:**
 - DB25M = 24V I/O
 - PB = Profibus DP Slave M12
 - PN = Profinet IO-Device M12
 - EIP = Ethernet/IP Device M12
 - ETH = Ethernet/Modbus M12
 - Module type**
 - HM = Main module
 - EM = Extension module
 - GM = Gateway module

				Surface	Scale	1:2	Position	Quantity
			Date	Name	MSTKN S24 Extension Module MSTKN-H-S24-EM-DB25M			
			11.08.2015	Bantele				
			Checked					
			Standard		Catalogue Number: 22300			
State	Changes	Date	Name	Filename	Assembly	S24_Extension_Module.iam	Page	Pg