



MSTKN - H - S14 - HM - DB25M - OP

Enclosure  
 H = Aluminium enclosure  
 P = Enclosure vor variable trays

Socket tray type  
 S = Single plugs Ø 38mm  
 T = Common block for standard bits  
 P = variable prismatic tray  
 M = Medium custom sockets  
 L = Large custom sockets

Socket number  
 13 = single row, 3 sockets  
 14 = single row, 4 sockets  
 18 = single row, 8 sockets  
 24 = two rows, 4 sockets per row  
 (total: 8 sockets)

Options  
 (none) standard  
 OP = Open Protocol

Interface type  
**Only for Modules HM and GM:**  
 DB25M = 24V I/O  
 PB = Profibus DP Slave M12  
 PN = Profinet IO-Device M12  
 EIP = Ethernet/IP Device M12  
 ETH = Ethernet/Modbus M12

Module type  
 HM = Main module  
 EM = Extension module  
 GM = Gateway module

		Surface	Scale	1:2	Position	Quantity
		Date	Name	<b>MSTKN P14 EA24</b> MSTKN-P-P14-HM-DB25M Catalogue Number: 22326		
		Drawn 19.07.2016	Bantele			
		Checked				
		Standard				
					Page	
State	Changes	Date	Name	Filename	Assembly P14 EA24.iam	Pg